

FEATURING DRIFT COLLECTION





DESIGNED BY Angela 🕉 Walters

QUILT DESIGNED BY



KIT QUA	NTITY
DFT-6306 DFT-6309 DFT-6309 DFT-6308 DFT-6300 DFT-6304 DFT-6302 PE-408 PE-445	7/4 yd. 1 3/8 yd. 5/8 yd. 5/8 yd. 5/8 yd. 5/8 yd. 5/8 yd. 2 1/8 yd. 1 yd.
Backing	5yds.



COLOR OPTION



Aquatic Lace Sapphire



Island Droplets Sky



by ANGELA WALTERS

DFT-5301 Island Droplets Celeste



DFT-5306 Blooming Algae Emerald



Feathered Coral Night

Gemmed Pathways Sea



Serenity Entwined Mist



Way to Zen Teal



Latticework Azure



Sea Foam Blue

DFT-6304

Latticework Turquoise



Aquatic Lace Bronze





Island Droplets Peach



Blooming Algae Gold





DFT-6307 Gemmed Pathways Terra



Serenity Entwined Pearl



ii ii

DFT-6309 Sea Foam Green



© 2014 Courtesy of Art Gallery Quilts LLC. All Rights Reserved. 3804 N 29th Ave. Hollywood, FL 33020 PH: 888.420.5399 FX: 425.799.6103



FABRIC REQUIREMENTS

DFT-6306	7/8 yd.
DFT-6301	1 3/8 yd.
DFT-6309	5/8yd.
DFT-6308	5/8yd.
DFT-6300	5/8yd.
DFT-6304	5/8yd.
DFT-6302	5/8yd.
PE-408	2 1/8yd.
PE-445	1yd.
	DFT-6301 DFT-6309 DFT-6308 DFT-6300 DFT-6304 DFT-6302 PE-408

Backing Fabric DFT-6306 5 yds. (suggested)

Binding Fabric DFT-6301 (Fabric B) (included)

CUTTING DIRECTIONS

 $^{1\!/}_{4}\!\!\!/''$ seam allowances are included.

FOR ROWS CUT


Twelve (12) 10" squares from fabric A Twelve (12) 10" squares from fabric B Eight (8) 10" squares from fabric C Eight (8) 10" squares from fabric D Eight (8) 10" squares from fabric E Eight (8) 10" squares from fabric F Eight (8) 10" squares from fabric G Eighteen (18) 4" x WTF strips from fabric H Eight (8) 4" x WTF strips from fabric I

*For color option replace fabrics with the fabrics from the OCEAN color way. except DFT-6306 that will be replaced by DFT-5307

BLOCK CONSTRUCTION


• Place a square from fabric H on the corner of a square from fabric A. Sew from corner to corner on the diagonal as shown in the diagram.

(DIAGRAM 1)




• Place a square from fabric I on the opposite corner and sew on the diagonal.

(DIAGRAM 2)




• Repeat on the remaining two corners with two more squares from fabric I

(DIAGRAM 3)



Trim all four corners, leaving a 1/4" seam
 allowance.
 (DIAGRAM 4)




Press the corner triangles open to complete the unit.
 (DIAGRAM 5)




• To make the fourth unit, use two neutral squares and two black squares as shown in the diagram.

(DIAGRAM 6)




 Lay out the four blocks as shown and sew together to complete the unit. (DIAGRAM 7)



Make 16 blocks in a variety of colors.

(DIAGRAM 8)





ASSEMBLING THE TOP

Sew all rights sides together with 1/4" seam allowance. Press open.

- Follow the cover photo to help you in the assembling of this quilt top. Start from the left following a vertical order. Press seams open as you sew.
- Lay out the 16 blocks in four rows of four blocks each. Refer to the assembly diagram to make sure the outside triangles from fabric H line up. Once you have the blocks placed as you like, sew together in rows and join the rows.

(DIAGRAM 9)





QUILT ASSEMBLY

Sew right sides together.

- Place BACKING FABRIC on a large surface wrong side up. Stretch it with masking tape against that surface.
- Place BATTING on top of backing fabric.
- Place TOP on top of the batting with right side facing up. Smooth away wrinkles using your hands.
- Pin all layers together and baste with basting thread, using long stitches. You can also use safety pins to join the layers.
- Machine or hand quilt starting at the center and working towards the corners. Remember that quilting motives are a matter of personal preference. Have fun choosing yours!
- After you finished, trim excess of any fabric or batting, squaring the quilt to proceed to bind it.

BINDING

Sew right sides together.

Cut enough strips 1½" wide by the width of the fabric
C to make a final strip 316" long. Start sewing the binding strip in the middle of one of the sides of the quilt, placing the strip right side down and leaving an approximated 5" tail. Sew with ¼" seam allowance (using straight stitch), aligning the strip's raw edge with the quilt top's raw edge.

- Stop stitching 1/4" before the edge of the quilt (DIAGRAM B 1). Clip the threads. Remove the quilt from under the machine presser foot. Fold the strip in a motion of 45° and upward, pressing with your fingers (DIAGRAM B2). Hold this fold with your finger, bring the strip down in line with the next edge, making a horizontal fold that aligns with the top edge of the quilt (DIAGRAM B3). Start sewing at 1/4" of the border, stitching all the layers. Do the same in the four corners of the quilt.
- Stop stitching before you reach the last 5 or 6 inches. Cut the threads and remove the quilt from under the machine presser foot. Lay the loose ends of the binding flat along the quilt edge, folding the ends back on themselves where they meet. Press them together to form a crease. Using this crease as the stitching line, sew the two open ends of the binding with right sides together (you can help yourself marking with a pencil if the crease is difficult to see).
- Trim seam to ¼" and press open. Complete the sewing. Turn binding to back of the quilt, turn raw edge inside and stitch by hand using blind stitch.



NOTE: While all possible care has been taken to ensure the accuracy of this pattern, we are not responsible for printing errors or the way in which individual work varies. Please read instructions carefully before starting the construction of this quilt. If desired, wash and iron your fabrics before starting to cut.

© 2014 Courtesy of Art Gallery Quilts LLC. All Rights Reserved.